

Dow Coating Materials

High gloss top coat based on Maincote 1200 Formulation SS454-105-E

Material Name	Kilograms	Liters	Level	
Grind				
Water	92.6	92.6		
Orotan 681	8.0	7.35	1.36%	% Disp
Triton HW-1000	5.6	5.25		
AMP-95	2.2	2.41		
Dowanol DPM	11.3	11.82	3.98%	% Coal
Ti -Pure TS-6200 ⁽¹⁾	195	48.75	15.50%	PVC
Grind Sub-total	313.3	166.84	15.50%	PVC
LetDown				
Maincote 1200	650	631.04		
Texanol	18.0	18.97	6.38%	% Coal
Vegerust NFP ⁽²⁾	10	3.94	1.25%	PVC
Acrysol RM-8W	5.6	5.42		
ВҮК-023	1.7	1.64		
Totals	1000.00	827.85		
Property	Value	(without additives)		
Total PVC	16.75	%		
Volume Solids	37.99	%		
Weight Solids	48.90	%		

(1) Ti -Pure TS-6200 from DuPont

(2) Vegerust NFP, vegetable anti flash rust from Labema Laboratories.

FASTRACK, KATHON, MAINCOTE, MULTILOBE, OROTAN, PARALOID, PRIMAL, ELASTENE, AVANSE, ROPAQUE, ROVACE, SKANE, ACRYSOL, RHOPLEX and TAMOL (in certain countries) are trademarks of Rohm and Haas Company, or of its subsidiaries or affiliates. The same goods may be marketed in other countries under other Company trademark designations.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee as conditions and methods of use of our products are beyond our control. We recommend that the prospective user determine the suitability of our materials and suggestions before adopting them on a commercial scale. Suggestions for uses of our products or the inclusion of descriptive material from patents and the citation of specific patents in this publication should not be understood as recommending the use of our products in violation of any patent or as permission or license to use any patents of the Rohm and Haas Company – The Dow chemical Company.